



(51) International Patent Classification:
F02P 1/08 (2006.01) *F02P 3/08* (2006.01)

(21) International Application Number:
PCT/SE2009/050112

(22) International Filing Date:
4 February 2009 (04.02.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0800280-0 7 February 2008 (07.02.2008) SE

(71) Applicant (for all designated States except US): SEM
AKTIEBOLAG [SE/SE]; P.O. Box 30, S-662 21 Åmål
(SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): OLSSON, Johan [SE/
SE]; Korsbyn 304, S-662 91 Åmål (SE).

(74) Agent: HYNELL PATENTTJÄNST AB; Patron Carls
väg 2, S-683 40 Uddeholm (SE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ,
EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO,
NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG,
SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR),
OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML,
MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A SYSTEM FOR ENERGY SUPPORT IN A CDI SYSTEM




Fig. 1

(57) Abstract: This invention relates to a method and system for generating energy/power in a capacitive discharge ignition system, said system comprising at least one charge winding (L) which by means of a fly wheel and via a first rectifier device (D1) charges a charge capacitor (C1) connected to a primary winding (P) of an ignition voltage transformer (30) in order to provide said primary winding (P) with energy for generation of a spark via a secondary winding (S) of said transformer (30), wherein a voltage control/switching unit (10) is arranged to enable output of energy (Out21) from said primary winding (P).

A SYSTEM FOR ENERGY SUPPORT IN A CDI SYSTEM

TECHNICAL FIELD

5 The present invention relates to a system and also a method for generating energy/power in a CDI system, said system comprising at least one charge winding which by means of a fly wheel and via a first rectifier device charges a charge capacitor connected to a primary winding of an ignition voltage transformer in order to provide said primary winding with energy for generation of a spark via a secondary winding of said
10 transformer.

PRIOR ART

Nowadays, various types of ignition systems are known and commonly used on the market, such as capacitive or inductive solutions. Most of those ignition systems have a
15 solution including some kind of battery support, e.g. US 6 557 537 and US 6 082 344, which in some applications strongly can be affected, due to environmentally causes e.g. humidity and temperature, and then have drastic consequences regarding performance and/or reliability. There are also cost, environmental and life time aspects to be considered when using a battery supported solution.

20 Ignition systems are known, without the use of battery support, and are also available on the market. However, known such systems all do show one or more disadvantages, seemingly due to accepting compromises regarding functionality to be able to eliminate battery support. It is known to, instead of battery support, use a separate small generator
25 which however presents some disadvantages such as additional cost. Also other solutions are known, for instance, EP0727578, which shows an inductive ignition-system, wherein power is (instead of battery) taken from a primary winding to control ignition timing, i.e. control of the spark advance, but without providing any other functionality that might be desired. Further, the control circuit as such is rather complex and rather inflexible.

30

BRIEF DESCRIPTION OF THE INVENTION

The object of the present invention is to provide an improved system for generating energy/power in a CDI system, which is achieved by means of a system as defined in claim 1.

35

Thanks to the invention a very flexible and cost effective solution is achieved, which may bring along about the same kind of functionality as battery powered systems, but which

at the same time eliminates the disadvantages related to battery supported systems. It is to be noted that the solution does not prevent usage of battery support, but as is evident provides the important technical advantage that battery support may be dispensed with.

- 5 Further advantages and aspects of the invention will be evident from the detailed description below.

DESCRIPTION OF THE FIGURES

The invention will be described in greater detail below with reference to the appended
10 figures, in which:

- Fig 1 shows a schematic wiring diagram presenting a voltage control/switching unit according to the invention integrated in a typical CDI system wherein several triggering alternatives are depicted,
15
- Fig. 2 shows in more detail a first alternative, depicted in Fig. 1, of an embodiment of the voltage control/switching unit according to the invention described in Fig. 1,
- Fig 3 shows in more detail a second alternative, depicted in Fig. 1, of an embodiment
20 of the voltage control/switching unit according to the invention described in Fig. 1.

DETAILED DESCRIPTION

Fig 1 shows a schematic wiring diagram consisting of a voltage control/switching unit 10
25 according to the invention integrated in a somewhat simplified form of a typical CDI system.

A brief description of the typical CDI system used in this example follows. The CDI system comprises of an iron core T1 provided with four conventionally arranged
30 windings, L, T, P and S, which are magnetised by means of one or several magnets integrated in the flywheel which at the rotation of the flywheel will sweep past the end portions of the iron core T1. The variant with several magnets could be used for providing (from a general point of view) a more powerful generator which in addition to the function as ignition voltage generator also could be used for other purposes, for
35 example fuel injection systems or handle heating on chain saws. The relative magnet movement induces a voltage in the windings L, T, P and S according to the following.

In a so called charge winding L, there is induced a voltage which is used for the spark generation, as such. The charge winding L is via one of its end points 1 connected via rectifier devices D1 to a charge capacitor C1, in which the energy will be stored until the spark will be activated, and to a thyristor Q1. The other end point 2 of the winding
5 L is connected to earth.

A so called trigger winding T is connected with a first end point 7 to earth and a second end point 8 to an input terminal In11 of an ignition control unit M1 and delivers to this input terminal information about the position and velocity of the flywheel and preferably
10 also power supply to the control unit M1, e.g. to the processor thereof. It could be noted that the control unit M1 may comprise of an only slightly modified version of a known, conventional control unit.

The third winding P constitutes the primary winding and the fourth winding S the
15 secondary winding of a transformer 30 for generating ignition voltage to a spark plug SP1. The end point 4 of the third winding P as well as the end point 5 of the fourth winding S is connected to earth.

In a conventional way an output terminal Out11 on the control unit M1 is activated
20 when the ignition voltage should be delivered to the spark plug. The switching device (the thyristor) Q1 having a trigger electrode of which is connected to the output terminal Out11 creates a current path to earth which results in the connection of the voltage over the capacitor C1 to the primary winding P. Initially a voltage transient is then generated in the secondary winding S due to the very high voltage derivative in the
25 connection point 12 at the anode of the thyristor Q1. Immediately thereafter the state in the transformer 30 changes into a damped self-oscillation in which the energy transits between the inductor P and the capacitor C1 through the switching device Q1.

The description above is simplified, and it is evident for the skilled person to foresee
30 other both resonant and non-resonant circuits for spark generation without departing from the scope of the invention.

According to the invention there is a voltage control/switching unit 10, that controls output of power, at Out21, from the primary winding P which power may be used to
35 drive a device (e.g. a sensor and/or a solenoid) externally of the ignition system. In the embodiment shown in Fig. 1 the voltage control/switching unit 10 is shown to have two input terminals In21 and In22 and one output terminal Out21. A first input terminal In22

is connected to the output terminal In12 on ignition control unit M1, and the second input terminal In21 is connected to the capacitor C1 and to the end 3 of the primary winding P via a connection point 11. The switching unit 10, is significant in that the switching (to the off mode) is only performed during a part of a complete revolution of the flywheel, and in such a way that the switching unit 10 is switched off for a desired time period (e.g. 100 μ s) for not disturbing the generation of the spark. Hence, a signal to In21 or In22 or both terminals In21 and In22 together, initiates or affects the switching unit 10 to switch off during a part of a revolution of the flywheel, before or in connection with, the said control unit (M1) initiating said spark, to not negatively affect said generation of spark. The rest of the time, the unit 10 is in its "on mode", whereby an output of about 0,5-2 W is obtained at Out21, at a flywheel speed of as low as 2000 rpm.

An optional connection 9, connecting the ignition control M1 and the voltage control/switching unit 10, enables a feedback and information about the charge/load level of a charge capacitor 14, described in Fig. 2, and the connection 9 can also be utilized for a change of the switch frequency etc. over the rpm.

The operation and method of the switching unit 10 according to the invention, and described in Fig 1 and 2, is such that the switching is managed/controlled by information from the in-signal on input terminals In21 and In22, either together or separately, dependent on specific needs/desires. For example if the system is set to be triggered by any in-signal and there is provided an in-signal to the input terminal In22 from the ignition control unit M1, based on information from the micro-processor therein, the switch control 19 will be controlled to switch off at a, regarding this kind of application, short period of time before the ignition control unit M1 will control the opening of the thyristor Q1, which starts the current flow through the primary winding P and generates the spark in SP1. Shortly after termination of the spark the control unit M1 will again close the thyristor Q1 and also activate the switch control 19 to be set in the on mode.

Fig. 2 shows in more detail a first embodiment of the voltage control/switching unit 10 according to the invention, that is indicated in Fig. 1, as one of the options to trigger/control the voltage control/switching unit 10. The voltage control/switching unit 10 is shown to comprise a switch control 19, a diode 13, a switch element 15 and a charge capacitor 14. The anode side of the diode 13 is connected to the input terminal In21 and the cathode side is connected to a first connector 16 of the switch element 15.

A second connector 18 of the switch element 15 is connected to the output terminal Out21 and to the charge capacitor 14.

The switch control 19, which controls the switching of the voltage control/switching unit 10, is connected to a connector 17 of the switch element 15 and to the input terminal

5 In22. For a skilled person it is evident that the switch element 15 may comprise various components available on the market e.g. a thyristor, a Triac etc. The purpose of the switch control 19 is to control that the switch element 15 is switched off during a desired (e.g. preset in the CPU of the control unit M1) period of time, e.g. 100 μ S, starting at or immediately before the generation of spark. In this embodiment the switching signals
10 In22 are controlled by software and/or hardware and a CPU in the ignition control M1, which normally implies conventional TTL-signals, e.g. a pulse signal at In21 some μ S before the initiating of the spark to put the switch element 15 in the off mode and a duration of about 100 μ S to switch back to the power generating mode. A purpose of the charge capacitor 14, connected between the output terminal Out21 and earth, is to
15 stabilize the output from terminal Out21, to provide energy to the external device when the switch element 15 is off.

Fig. 3 shows in more detail a second embodiment of the switching unit 10 according to the invention, depicted in Fig. 1 as one of the options. The switching unit 10 comprises,
20 of a Triac or thyristor or other suitable switching element 21, a spark initiation detection unit 25, the capacitor 14 and the switch control 19. Whereof one power terminal 22 of the Triac 21 is connected to the input terminal In21 (which is corresponding to the diode 13 in Fig 2) and a second power terminal 23 is connected to the output terminal Out21. The capacitor 14, connected between the output terminal Out21 and earth, is stabilizing
25 the outgoing voltage of the output terminal Out21, i.e. supplying power during the off mode of the control/switching unit 10. The switch control 19, which controls the switching of the switching unit 10, is connected to the gate 24 of the Triac 21 (which is corresponding to the switch element 15 in Fig 2). The spark initiation detection unit 25, which is integrated in the switch control 19, is connected via a connection S21 to the
30 input terminal In21 which means, according to this example, that the voltage control/switching unit 10 is connected to the CDI system via the connection In21 only.

The operation and method of the switching unit 10 shown in Fig 3, is such that the switching is managed/controlled by information from the in-signal on the input terminal
35 In21, which is given by the voltage transient (amplitude and/or pulse-form) in the primary winding P created when initiating the spark generation which is detected by the spark initiation detection unit 25, which in turn generates a signal to the switch control

19, whereby the switch control 19 immediately switches off the voltage control/switching unit 10. The core of the switch element in this embodiment is the Triac 21 that switches off during a certain period of time, e.g. in the range of 80-120 μ S. In this embodiment the signal to switch off is not generated before the start of generation of the spark but a short
5 time (e.g. $\leq 5 \mu$ S) after the start, due to the use of a detection unit 25. Accordingly the specific period of time in the off mode starts immediately after the generation of spark is initiated. When the generation of spark is ended the voltage control/switching unit 10 is switched back to the power generating mode.

10 It is evident that in conformity with other known spark generating CDI systems the switching may preferably be controlled by the amplitude or pulse-form of the primary winding P, wherein the signals and current flow is caused by the magnetism of the passing flywheel. Accordingly, e.g. the detection of a negative pulse on the primary
15 winding P may be used to cause an immediate interrupt i.e. an immediate switch off of the voltage control/switching unit 10 or possibly, if desired, with a preset delayed or premature triggering. Hence, a very flexible means of controlling due to the fact that the control unit 10 may be flexibly set with a great variety of (desired) triggering parameters.

In preferred embodiments intended to be used primarily in connection with small
20 engines (e.g. chain saws) the components of a system according to the invention may be chosen within a wide range to provide the functionality as intended by the invention. However, there are some basic requirements, e.g. that there is a charge winding L that is sufficiently powerful to generate needed energy, i.e. within the range of 1-15 mWs.

25 Summarized, one advantage of the switching unit 10 according to the invention is the ability to utilize the primary winding for generation of an electrical power, and this in alignment with a very low impact on the performance of the CDI system, i.e. the sparking generation, and regarding burn-time, ignition voltage, energy and the peak power. The generated energy/power can be used for supplying of internal or external
30 units e.g. sensors, solenoids.

The invention is not limited by the embodiments described above but may be varied within the scope of the appended claims. For instance the skilled person realizes that several external units may be connected to Out21 and that for instance at a higher rpm,
35 which produces a higher output then could be arranged for connecting a further external device, e.g. fuel mixture meter, battery charging, sensors or other small power demanding devices. Further, the skilled person realizes that many other evident

modifications, may be made within the scope of protection, e.g. using a further winding (or several), in series with the primary winding, to achieve the desired voltage.

- 5 Regardless of form of embodiment, the switch unit 10 can also be used for limiting output power. This can be implemented as a voltage control device which then will regulate output voltage by switching unit 10 on/or off as a reaction to variations in both output load and engine rpm.

CLAIMS

1. System for generating energy/power in a capacitive discharge ignition system, said system comprising at least one charge winding (L) which by means of a fly wheel and via a first rectifier device (D1) charges a charge capacitor (C1) connected to a primary winding (P) of an ignition voltage transformer (30) in order to provide said primary winding (P) with energy for generation of a spark via a secondary winding (S) of said transformer (30), characterized by a voltage control/switching unit (10) arranged to enable output of energy (Out21) from said primary winding (P), and also disrupt output of energy (Out21) during a limited period of time each revolution of the flywheel.
2. System according to claim 1, characterized by providing power from said primary winding (P) to at least one external device.
3. System according to claim 2, characterized by said external device including at least one of the following:
 - a) CPU-unit.
 - b) a solenoid
 - c) a sensor
4. System according to any of claims 2 or 3, characterized in that there is an ignition control unit (M1) controlling said voltage control/switching unit (10).
5. System according to any preceding claim, characterized by said system having no battery support.
6. System according to claim 1, characterized in that said voltage control/switching unit (10) is controlled to supply said power by being activated and that in activation is controlled to be maintained merely for the duration of generated sparks.
7. System according to Claim 6, characterized by the said voltage control/switching unit (10) being directly controlled by means of a first signal (In22) from said ignition control unit (M1).
8. System according to Claim 6 or 7, characterized by the said voltage control/switching unit (10) being indirectly controlled by means of a second signal (In21), related to a voltage transient from the primary winding (L).

9. System according to any of claims 1-8, characterized in that said voltage control/switching unit (10) comprises a rectifying component (13; 21), preferably in the form of a rectifier diode (13) or a Triac (21).

5 10. System according to any of claims 1-9, characterized by a load (14) connected to the output (Out21) from said voltage control/switching unit (10).

11. System according to claim 10, characterized by said load (14) being a capacitor or a similar energy supplying component.

10

12. Method for controlling a system according to any of claims 1-11, characterized by having said voltage control/switching unit (10) switched off during a short period of time in connection with spark generation before either starting or initiating said spark, or shortly after.

15

13. Method according to claim 12, characterized by using a thyristor (Q1) which initiates the current flow through said primary winding (P), which in turn generates the spark.

20 14. Method according to claim 12, characterized by using the pulse (IN21) from the primary winding (P) to deactivate said voltage control/switching unit (10).

15. Method according to claim 12, characterized by a connection (9), connecting a ignition control unit (M1) and the voltage control/switching unit (10), enabling feedback
25 and information about the charge/load level of a charge capacitor (14) in said voltage control/switching unit (10).




Fig. 1




Fig. 2




Fig. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE2009/050112

A. CLASSIFICATION OF SUBJECT MATTER

IPC: see extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: F02P, G05F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0597352 A2 (DUCATI ENERGIA S.P.A), 18 May 1994 (18.05.1994), column 4, line 16 - column 5, line 2, figure 1, abstract --	1-15
A	EP 0727578 A2 (DUCATI ENERGIA S.P.A), 21 August 1996 (21.08.1996), figure 3, abstract --	1-15
A	EP 0646723 A1 (HONDA GIKEN KOGYO KABUSHIKI KAISHA), 5 April 1995 (05.04.1995), figure 1, abstract -- -----	1-15

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

15 May 2009

Date of mailing of the international search report

19-05-2009

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Cecilia Håkansson/Eö
Telephone No. +46 8 782 25 00

International patent classification (IPC)**F02P 1/08** (2006.01)**F02P 3/08** (2006.01)**Download your patent documents at www.prv.se**

The cited patent documents can be downloaded:

- From "Cited documents" found under our online services at www.prv.se (English version)
- From "Anförda dokument" found under "e-tjänster" at www.prv.se (Swedish version)

Use the application number as username. The password is
ATNGAZORXC.Paper copies can be ordered at a cost of 50 SEK per copy from
PRV InterPat (telephone number 08-782 28 85).

Cited literature, if any, will be enclosed in paper form.

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/SE2009/050112

EP	0597352	A2	18/05/1994	IT	1256379 B	04/12/1995
EP	0727578	A2	21/08/1996	SE	0727578 T3	
				AT	211218 T	15/01/2002
				DE	69618041 D,T	13/06/2002
				ES	2164791 T	01/03/2002
				IT	1275159 B	30/07/1997
				IT	MI950278 A	15/08/1996
EP	0646723	A1	05/04/1995	BR	9403994 A	18/07/1995
				CN	1052528 C	17/05/2000
				CN	1109554 A	04/10/1995
				DE	69403420 D,T	18/09/1997
				JP	3201684 B	27/08/2001
				JP	7103112 A	18/04/1995